

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancel)
2. (Cancel)
3. (Cancel)
4. (Cancel)
5. (Cancel)
6. (Cancel)
7. (Cancel)
8. (Cancel)
9. (Cancel)
10. (Cancel)
11. (Cancel)

D-3212
Appl. No. 11/536,659
Reply to Office Action of January 22, 2009

12. (Cancel)

13. (Cancel)

14. (Cancel)

15. (Cancel)

16. (Cancel)

17. (Cancel)

18. (Cancel)

19. (Cancel)

20. (Cancel)

21. (Cancel)

22. (Cancel)

23. (Cancel)

24. (Cancel)

25. (Cancel)

26. (Cancel)

Claims 27-34 (Canceled)

35. (Cancel)

36. (Previously presented) A method of separating CO₂ from a gas stream containing CO₂ and an anaesthetic gas, which comprises transporting the gas stream at a periodically varying flow rate through the gas separation device, said device comprising a supported carrier liquid membrane in which the carrier species is an organic base present at a concentration sufficient to provide a separation factor α (CO₂, a),

$$\text{where } \alpha (\text{CO}_2, a) = \frac{R_{\text{CO}_2}}{p_{\text{CO}_2}} \cdot \frac{p_a}{R_a}$$

wherein R represents permeation rate, p partial pressure of a gas in the feed gas stream and a an anaesthetic gas, greater than unity.

37. (Previously presented) A method for separating gases in a gas stream, which comprises contacting the gas stream comprising carbon dioxide and an anaesthetic gas with a supported carrier liquid membrane in which the carrier is an organic base present in a concentration of at least 4.5 mol.dm⁻³.

38. (Cancel)

39. (Previously presented) A method as claimed in claim 37, in which the gas stream is transported at a periodically varying flow rate over the supported carrier liquid membrane.

40. (Previously presented) A method as claimed in claim 36, wherein the device comprises a supported carrier liquid membrane in which the carrier species is present in a concentration of at least 4.5 mol.dm^{-3} .

41. (Previously presented) A method as claimed in claim 36, wherein the membrane is a hollow fibre membrane, and is in the form of a fibre bundle.

42. (Previously presented) A method as claimed in claim 36, which further comprises generating a sweep gas stream or providing a vacuum on a face of the membrane remote from the gas stream.

43. (Previously presented) A method as claimed in claim 42, which further comprises humidifying the sweep gas stream.

44. (Previously presented) A method as claimed in claim 37, wherein the membrane is a hollow fibre membrane, and is in the form of a fibre bundle.

45. (Previously presented) A method as claimed in claim 37, which further comprises generating a sweep gas stream or providing a vacuum on a face of the membrane remote from the gas stream.

46. (Previously presented) A method as claimed in claim 45, which further comprises humidifying the sweep gas stream.

47. (Currently amended) Apparatus for separating CO₂ from a gas stream containing CO₂ and an anaesthetic gas, the apparatus comprising a gas separation device and means comprising a bellows ventilator for transporting the gas stream at a sinusoidally varying flow rate through the gas separation device, the device comprising a supported carrier liquid membrane in which the carrier species is an organic base present at a concentration sufficient to provide a separation factor α (CO₂, a),

$$\text{where } \alpha (\text{CO}_2, a) = \frac{R_{\text{CO}_2}}{P_{\text{CO}_2}} \cdot \frac{p_a}{R_a}$$

wherein R represents permeation rate, p partial pressure of a gas in the feed gas stream and a an anaesthetic gas, greater than unity.

48. (Cancel)

49. (Previously presented) Apparatus as claimed in claim 47, wherein the device comprises a supported carrier liquid membrane in which the carrier is present in a concentration of at least 4.5 mol.dm⁻³.

50. (Previously presented) Apparatus as claimed in claim 47, wherein the membrane is a hollow fibre membrane, and is in the form of a fibre bundle.

51. (Previously presented) Apparatus as claimed in claim 47, which further comprises means for generating a sweep gas stream

or means for providing a vacuum on a face of the membrane remote from the gas stream.

52. (Previously presented) Apparatus as claimed in claim 51, which further comprises means for humidifying the sweep gas stream.

53. (New) A method as claimed in claim 36, wherein the organic base is selected from the group consisting of diethanolamine, ethanolamine and ethylenediamine.

54. (New) Apparatus as claimed in claim 47, wherein the organic base is selected from the group consisting of diethanolamine, ethanolamine and ethylenediamine.

55. (New) Apparatus for separating CO₂ from a gas stream containing CO₂ and an anaesthetic gas, the apparatus comprising a gas separation device and a means for transporting the gas stream at a sinusoidally varying flow rate through the gas separation device, the means comprising a bellows ventilator, the device comprising a supported carrier liquid membrane in which the carrier is an organic base present in a concentration of at least 4.5 mol.dm⁻³.

56. (New) Apparatus as claimed in claim 55, wherein the membrane is a hollow fibre membrane, and is in the form of a fibre bundle.

D-3212

Appl. No. 11/536,659

Reply to Office Action of January 22, 2009

57. (New) Apparatus as claimed in claim 55, which further comprises means for generating a sweep gas stream or means for providing a vacuum on a face of the membrane remote from the gas stream.

58. (New) Apparatus as claimed in claim 57, which further comprises means for humidifying the sweep gas stream.

59. (New) Apparatus as claimed in claim 55, wherein the organic base is selected from the group consisting of diethanolamine, ethanolamine and ethylenediamine.